

6 SILENT BELT DRIVEN

6.1 WITHOUT TANK



TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX49GSIL/4	BX49G	-	4	380	541	10	1400	96 X 66 X 80	132
BX59GSIL/5,5	BX59G	-	5,5	380	606	11	1400	96 X 66 X 80	150
BX60GSIL/7,5	BX60G	-	7,5	380	798	11	1400	96 X 66 X 80	165
BX70GSIL/10	BX70G	-	10	380	1246	11	1320	104 X 74 X 87	190
BX80GSIL/15	BX80G	-	15	380	1505	11	1320	104 X 74 X 87	200

WITH STAR DELTA STARTER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX59GSIL/5,5 SDS	BX59G	-	5,5	380 ΔΔ	606	11	1400	96 X 66 X 80	154
BX60GSIL/7,5 SDS	BX60G	-	7,5	380 ΔΔ	798	11	1400	96 X 66 X 80	169
BX70GSIL/10 SDS	BX70G	-	10	380 ΔΔ	1246	11	1320	104 X 74 X 87	194
BX80GSIL/15 SDS	BX80G	-	15	380 ΔΔ	1505	11	1320	104 X 74 X 87	204